

The Single Sided Tacky Roller Cleaning Machine provides an unequaled system for continuous contact cleaning. Specially formulated polymer rollers lift and transfer contaminates from your product surface to adhesive rolls. No special chemicals, wipes, or handling needed.



IDEAL APPLICATIONS

- Cleaning flexible material in reel-to-reel applications
- · In-line processes in converting, coating, printing, etc.
- Films, label printing, holographics, flexographics, packaging, etc.
- · For Web Widths 24 44 inches

At the most critical stages in your process (e.g. just prior to printing, etc.), the MKWCS will both clean and neutralize the charge on your substrates.







a (SDI



- High level cleaning efficiency
- Speeds up to 1000 FPM
- Adjustable preload to assure conformity to the cleaned surface
- Versatile Mounting
- Anti-Static

REQUIREMENTS

- 110VAC or 220VAC
- Air Supply for (60 P.S.I)


OPTIONS


(SDI

- Linear material counter
- Programmable alarm, paper auto-release
- Non-silicone cleaning system
- Speed match for adhesive rolls

THE CLEANING PROCESS

Special polymer rollers lift the contaminate from the panel and transfers them to the adhesive roll. When the adhesive roll becomes laden with contaminate, simply strip the outer layer exposing a new clean surface of adhesive. Anti-static bars neutralize product, preventing re-contamination.





DIM	CLEANING WIDTH (CW)
Α	25.4 (645 mm)
В	CW + 8.85" (CW + 225 mm)
С	7.85" (199 mm)
D	12.3" (312 mm)
Е	CW-10" (CW-254 mm)
F	CW-1.2" (CW - 30 mm)
G	7.2" (183 mm)





* Custom sizes available



21 Morgan Irvine, CA 92618 U.S.A. Phone (949) 583-1001 Fax (949) 583-7007 www.sdionline.com